Digital Mini Current Clamp APPA A2

APPA A2 & A3 Top of Low-cost Electrical Testers

Key Functions

- 1999 count digital display
- AC current measuring capability up to 400Amps

General Information

- Data Hold
- Max Hold
- Battery door easy to replace battery
- Up to 27mm dia. (500MCM) Conductor size
- 4 feet Drop Proof
- Hand Guard & Stream Line Designed
- CAT. III 600V Safety Standard
- Carrying Case included

Technical Data		
Display 3 1/2 Digital, LCD, 1999 Digits		
Current AC	Range	200.0A, 400A
	Basic Accuracy	±(1.9%+5d) 50Hz~60Hz
	Conversion Type	Average sensing RMS indicating
Continuity Beeper	Threshold	<50Ω
	Indicator	2kHz tone buzzer
Sampling Rate	1.5 times/sec	
Overload Indication	"OL" or "-OL"	
Lower Battery Indication		
Auto Power Off	Approx. 10minutes	
Operating Temperature	-20℃~ 50℃, <80% RH	
Storage Temperature	-20℃~ 60℃	
Temperature Coefficient	0.15(Spec. Acc)/℃, <18℃ or >28℃	
Safety	IEC 61010 and designed to meet UL61010 specifications CAT. III 600V	
Maximum Conductor Size	27mm dia. (500MCM)	
Maximum Jaw Opening	31mm ida.	
Power Requirement	Single 9V battery (NEDA 1604 or IEC 6F22)	
Battery Life	200 hours	
Size	56mm (W) x 180mm (L) x 32mm (H)	
Weight	250 g	
Included with Instrument	Test Leads, ZnC battery (installed), Manual, and Carrying case	

Agent: Shanghai Beihan
TEL:+86-21-63340274 63340254
FAX:+86-21-63340789-808