



## Mini Digital Multimeters APPA 62/62R

### APPA New 60 Series Top of Low-Cost

#### Key Functions

- 2000 count large scale digital display
- Autoranging and manual selection
- ACV, DCV, Ohm, Continuity and Diode function
- **True RMS reading on AC mode (62R)**
- 0.5% basic DCV accuracy
- Data Hold
- VoltSense feature (None Voltage Detecting)
- AC/DC 10 Amps
- MAX/MIN function key
- Frequency Counter
- Capacitor measurement

#### General Information

- Auto Power Off
- Shock proof from 4 feet drops
- Probe holder and tilt stand
- Soft grips for over molding
- CAT III 600V Safety Standard

Technical Data		
Display 3 1/2 Digital, LCD, 1999 Digits		
Voltage AC	Range	200.0mV~750V
	Basic Accuracy	±(1.5%+5d)at 50Hz~500Hz
Voltage DC	Range	200.0mV~1000V
	Basic Accuracy	±(0.5%+5d)
Current AC	Range	2.000, 10.00A
	Basic Accuracy	±(1.5%+5d)
Current DC	Range	2.000, 10.00A
	Basic Accuracy	±(1.0%+3d)
Resistance	Range	200.0Ω~20MΩ
	Basic Accuracy:	±(0.7%+2d)
Continuity Beeper	Threshold	<150Ω, 2KHz tone buzzer
Diode Test	Open circuit Voltage	2V
Capacitance	Range	2.000nF~2.000mF
	Basic Accuracy:	±(1.9%+8d)
Sampling Rate	1.5 times/sec	
Auto Power Off	Approx. 10 minutes	
Operating Temperature	-20 ~ 50 , <80% RH	
Storage Temperature	-20 ~ 60	
Temperature Coefficient	0.15(Spec. Acc)/ , <18 or >28	
Safety	CAT III 600V Safety Standard IEC61010 and designed to meet UL61010 specifications	
Power Requirement	IEC LR03, AM4 or AAA size 1.5V x 2	
Battery Life	250 hours (Alkaline battery)	
Size	74mm (W) x 156mm (L) x 44mm (H)	
Weight	250 g	
Included with Instrument	Test Leads, ZnC battery (installed) and manual	

**Agent: Shanghai Beihan**

TEL:+86-21-63340274 63340254

FAX:+86-21-63340789-808

