

## HIGH VOLTAGE PROBE

PD-28/PD-28S are high voltage probes. They measure both AC and DC voltages with your multimeter. They consist of 2 kinds of contact tips, a test clip for the ground, a set of test leads for multimeter and a high quality enclosure.

The enclosure has very good insulation properties.

They are light-weight and rugged.

2 kinds of contact tips are available.

One is a round needle tip for normal use.

Another is a special flat spring type for CRT anode.

Before taking any measurements, first connect the alligator clip of this probe to earth ground and make sure connection is proper.



● For scope.  
PD-28S

CE

PD-28

- PD-28 have the same shape and color but different specifications.
- Meets IEC/EN 61010-1  
IEC/EN 61010-2-031

### SPECIFICATIONS

#### PD-28/PD-28S

Input Impedance	1000 M $\Omega$
Attenuation Ratio	1000 : 1
Accuracy	DCV (0 ~ 20kV) $\pm 1\%$ , DCV (20kV ~ 40kV) $\pm 2\%$ ACV (0 ~ 28kV) typically $\pm 5\%$ at 60 Hz
Max.Working Voltage	40kV DC or 28kV AC
Operating Temperature	0°C ~ 50°C
Storage Temperature	-10°C ~ 60°C
Cable Length	1 m
Weight	Approx. 260g

●Note: PD-28 is a high voltage probe that is used with DMM

Authorized Distributor of SEW in China

Shanghai beihan Electronics Co.,Ltd

TEL: 86-21-63340274 63340254 FAX: 86-21-63340789

<http://www.beha.com.cn>

e-mail: [info@beha.com.cn](mailto:info@beha.com.cn)