

## CLAMP METER



### 3810 CL TRUE RMS

#### FEATURES

- Full autorange for V.A and  $\Omega$  functions.
- Data hold function freezes the reading in dimly lit or hard to reach places.
- Low battery indication.
- Built-in buzzer for continuity test.
- Safety design throughout with no exposed metal parts. Shielded banana plugs and recessed input terminals.
- Ohm function ideal for checking continuity of relays, transformers and motor coils.

#### SPECIFICATIONS

Model	(Auto-Ranges)
ACA	400/1000A $\pm(1.5\%rdg+3dgt):40-500Hz$
ACV	400/600V $\pm(1.0\%rdg+3dgt):40-500Hz$
DCA	400/1000A $\pm(1.5\%rdg+3dgt)$
DCV	400/600V $\pm(0.75\%rdg+3dgt)$
$\Omega$	2000 $\Omega$ $\pm(1.0\%rdg+3dgt)$
Buzzer Sounds	<100 $\Omega$
Conductor Size	40mm Max.
Low Battery Indication	
Dimensions	255(L) x 80(W) x 35(D)mm
Weight (Battery Included)	Approx. 420g
Power Source	9V (6F22.006p) x 1 battery
Accessories	Test leads (TEL-AL11-1) Carrying case Instruction manual Battery
Safety Standard	EN 61010-1 EN61010-2-32 CAT III 600V

Authorized Distributor of SEW in China

Shanghai beihan Electronics Co.,Ltd

TEL: 86-21-63340274 63340254 FAX: 86-21-63340789

<http://www.beha.com.cn>

e-mail: [info@beha.com.cn](mailto:info@beha.com.cn)